COMBINED TECHNICAL SERVICES EXAMINATION (INTERVIEW POST)

COMPUTER BASED TEST

DATE OF EXAM: 21.07.2025 AN

PAPER - II - MINING ENGINEERING

(DEGREE STANDARD) (CODE: 347)

- 1. In an underground mine the sump has a peak inflow as 1 meter cube/minute. The capacity of pumping (Installed) in the mine must be
 - (A) Greater than 1 metre cube/minute
 - (B) Less than 1 metre cube/minute
 - (C) Equal to 1 metre cube/minute
 - (D) Equal to 2 metre cube/minute
 - (E) Answer not known
- 2. In the context of mining engineering, what is the primary purpose of implementing Computer Aided Design (CAD) systems?
 - (A) To automate the operation of mining equipment
 - (B) To enhance the accuracy and efficiency of Mine design and planning
 - (C) To monitor real time environmental conditions in mines
 - (D) To manage the supply chain of mined materials
 - (E) Answer not known
- 3. In GIS, a "buffer" analysis is used to:
 - (A) Reduce fire size
 - (B) Add colors
 - (C) Determine area around a feature
 - (D) Backup project files
 - (E) Answer not known

- 4. What is one application of remote sensing in mining? Processing dispatch (A) (B) Environmental monitoring (C) Survey drafting Payroll automation (D) (E) Answer not known What is the role of data loggers in SCADA? 5. Visualization (A) (B) Real-time user feedback (C) Storing and analyzing sensor data Drawing layouts (D) Answer not known (E)The use of microwave sensors in mining is primarily for 6. (A) Communication (B) Weather detection (C) Moisture measurement in stock piles (D) Drafting (E) Answer not known 7. An examples of integrating GIS with remote sensing in mining is: Exporting, .dwg filer (A)
 - (C) Drafting conveyor plans

Analyzing Landsat images

- (D) Creating ERP modules
- (E) Answer not known

8.	The	benefit of using LIDAR in r	nning is:	
	(A)	Measuring mine output		
	(B)	Real-time monitoring		
	(2)	Creating high-resolution s	urface maps	
	(D)	Automating vehicle dispat	ch	
	(E)	Answer not known		
9.		CAD, mine design primarily nats?	uses which of the following draw	/ing
	(A)	.csv	(B) .dwg	
	(C)	.pdf	(D) .shp	
	(E)	Answer not known	2	
10.	Whi krig		d for statistical Geostatistics	like
	(A)	MS Excel	(B) SURPAC	
	(C)	Auto CAD	(D) Oracle	
	(E)	Answer not known		
11.	The	spatial component in GIS r	efers to	
	(A)	Mining volume	(B) Numerical output	
	45	Geographic location	(D) Time-bound data	
	(E)	Answer not known	~ /	

12.	Data	a Loggers in SCADA are used	for	
	(A)	Report informating		
	(B)	Dynamic modelling		
	(6)	Historical data storage	100	
	(D)	Security control		
	(E)	Answer not known		
13.	The	use of AutoCAD in mining co	ntribu	tes to
	(A)	Data transfer	(B)	Equipment repair
	(6)	Drafting mine plans	(D)	Communications
	(E)	Answer not known		
14.	Whi	ch is not RDBMS software?		
	(A)	Oracle	(B)	SQL
	(0)	Excel	(D)	DB2
	(E)	Answer not known		
15.	Whi	ch is not part of structured pr	ogram	ming?
	(A)	Top down approach	(B)	Object
	(C)	Bottom-up approach	(D)	Sequence
	(E)	Answer not known		
16.	Whi	ch is not component of storage	e mana	ager of DBMS?
	(A)	Authorization	(B)	Transaction
	(C)	Buffering	(B)	Manipulation
	(E)	Answer not known		

17.	Which is not application of artificial intelligence?		l intelligence?
	(A)	Face recognition system	
	(B)	Chat bots	
	(C)	LIDAR	ž.
	(B)	DBMS	
	(E)	Answer not known	
18.	Whi	ch is the structured programmi	ng?
	(A)	C++	(B) C
	40)	Visual C++	(D) Java
	(E)	Answer not known	
19.	appr 40%	raisal A, B, C and D with we	em, there are four criterias for ightages of 10%, 20%, 30% and s scores of 3.5, 3.8, 4.2 and 3.5 in ined average is
	(A)	3.75	(B) 3.77
	(C)	3.79	(D) 3.80
	(E)	Answer not known	
20.	Mar	ginal analysis can be used to co	mpare
	(A)	Cost	
	(B)	Revenue	
	(0)	More revenue due to more cos	t
	(D)	Loss due to costs	

(E)

Answer not known

7

21. A drilling machine is expected to drill 60 meters per shift, to delays, it only drills 45 meters. What is the efficiency percent			- IV		
	to delays	, it only drills 45	meters. wn	0.0	•
	(A) 65	%	9	B)	75 %
	(C) 85	%	()	D)	95 %
	(E) Ans	swer not known			
22.	A mining	g project has thre	ee-time estim	nat	es
	- Optim	istic time (O)	= 10 days		
	- Most l	ikely time (M)	= 15 days		
	- Pessin	nistic time (P)	= 25 days		
	Using PI	ERT, what is the	expected pro	oje	ct duration
	(A) 15.	00 days	4	B)	15.83 days
	(C) 16.	5 days	(1	D)	17.5 days
	(E) Ans	swer not known			
23.	has relia		ne pumps we	_	were to connected in series to be connected in parallel
	(A) 0.2	1	(B)	0.60
	(6) 0.9	1	(D)	0.95

(E) Answer not known

24.		ch of the following earnings is not included in the "Ordinary of wages" of mine employees?
	(A)	Basic wages
	(B)	Dearness Allowance
	(6)	Bonus excluding incentive for production
	(D)	Compensation in cash
	(E)	Answer not known
25.	For a	a linear programming problem, identify the incorrect statement.
	(A)	Optimal point lies in one of the corner points
	(B)	Objective function is linear
	(C)	All the constraints are linear
	(D)	Optimal point lie in any one of the interior points of the feasible region
	(E)	Answer not known
26.	Whi	ch is not objectives of network analysis?
	(A)	To complete project in stipulated time
	(B)	Optimum utilization of available resources
	(C)	Minimize of cost and time
	(B)	Maximize investment in inventory
	(E)	Answer not known
27.	Whi	ch is not the tools or techniques of project management?
	(A)	Milestone charts (B) Simulation
	(C)	PERT (D) CPM
	(E)	Answer not known

28.	Whi	ch is not part of linear progra	mming model formulation?	
	(A)	Objective function	(B) Variable	
	(e)	Optimum value	(D) Constraints	
	(E)	Answer not known		
29.	Whi	ch is not limitations of operat	cions research?	
	(A)	Emotional factors		
	(B)	Resistance by the employees	S	
	(C)	Numerous quantity and est	ablishing relations factor	
	(D)	Scientific factors		
	(E)	Answer not known	**	
30.	intro	3.56	ntelligence has been developed el in mineral process control	
	(A)	Binary matrix	(B) Fuzzy logic	
	(C)	Expert System	(D) Numerical modeling	
	(E)	Answer not known		
31.		at is a distinguishing feat essing?	cure of stirred mills in min	iera)
	(A)	They use large grinding med	dia for coarse grinding	
	(8)	They employ a shaft with p grinding	oins or disks for fine and ultra-	fine
	(C)	They use centrifugal force to	o separate particles	
	(D)	They operate only for grindi	ing larger particles (> 500 μm)	
	(E)	Answer not known	चन्द्र करून <u>व्यव</u> ्य क्षेत्र हैं।	

- 32. Hammer mill is a type of:
 - (A) Compression crusher

(B) Impact crusher

(C) Attrition grinder

(D) Roller crusher

- (E) Answer not known
- 33. What is a key characteristic of the brake jaw crusher?
 - The jaw is pivoted at the top, resulting in a fixed receiving area and valuable discharge opening
 - (B) The jaw is pivoted at the bottom, allowing a fixed discharge and variable feed opening
 - (C) Both jaws are fixed and the material is crushed by vibration
 - (D) It uses rotating hammers for impact crushing
 - (E) Answer not known
- 34. What does free settling refer to in mineral processing?
 - (A) Settling of particles in a confined and crowded fluid medium
 - (B) Sinking of particles in a large volume of fluid relative to the particle volume
 - (C) Settling of particles due to electrostatic forces
 - (D) Sinking of particles only under centrifugal force
 - (E) Answer not known

- 35. What is the primary purpose of the jigging process in mineral processing?
 (A) To grind the ore into fine particles
 (B) To separate magnetic materials from non-magnetic ores
 (C) To separate minerals from gangue based on the colour
 (D) To separate minerals from gangue based on specific gravity
 - (E) Answer not known

differences

36. Jigging is done based on difference in

(A) Density

(B) Mass

(C) Volume

(D) Terminal velocity

- (E) Answer not known
- 37. The mill which accepts the lowest size of feed is
 - (A) Rod mill
 - (B) Ball mill
 - (C) Autogenous mill
 - (D) Spherical mill
 - (E) Answer not known

38. The coordinates of three points A, B and C are as follows

Latitude

Departure

A 769 N (meter)

823 meter (E)

B 447 N (meter)

674 meter (W)

C 835 S (meter)

100 meter (W)

The area of the triangle ABC is

- (A)
- 1,051, 934.2 meter²
- (B) 1,051, 930.1 meter²
- (C) 1,051, 942.2 meter²
- (D) 1,051, 936.2 meter²
- (E) Answer not known
- 39. A coal seam is located at a depth of 500 meters at A with a DIP of 10 degrees and direction of N 45° E from A. B is at a distance of 2000 m, 30 m higher than A and bearing of AB is S60 E. The coal beam at B is at a depth of
 - (A) 628.1 meters

(B) 621.3 meters

(C) 620.1 meters

- (D) 619.3 meters
- (E) Answer not known
- 40. DGPS stands for
 - (A) Different Global Positioning System
 - (B) Direct Global Positioning System
 - Differential Global Positioning System
 - (D) Dynamic Global Positioning System
 - (E) Answer not known

41.		at will be quadrant bearing of 36° 25'	a line	e whose whole circle bearing
	(A)	S 56° 25' W		
	(B)	N 56° 25' W		
	(C)	S 56° 25' E		
	(D)	S 43° 45' E		
	(E)	Answer not known		
42.	Poor	focusing is a source of		
	(A)	Instrumental error	(B)	Personal error
	(C)	Natural error	(D)	Resolution error
	(E)	Answer not known		
43.	Perr	missible limit of error for direct	trav	erse in correlation is
	SK	± 1 minute of ARC	(B)	± 2 minute of ARC
	(C)	± 3 minute of ARC	(D)	± 4 minute of ARC
	(E)	Answer not known		
44.	and chai	distance between two stations found to be 1500 mtrs. The sen and found to be 1476 mtrs. t, what was the error in the 30	ame If th	was measured with a 30 m ne 20 m chain was 5 cm too
	(1)	41 cm too long	(B)	45 cm too long
	(C)	50 cm too long	(D)	60 cm too long
	(E)	Answer not known		

- 45. The bearing of a line that is measured with magnetic North (or South) in a clockwise direction is termed as
 - (A) Reduced bearing
 - (B) True bearing
 - Whole circle bearing
 - (D) Fore bearing
 - (E) Answer not known
- 46. In old map, a line AB was drawn to a magnetic bearing of 5° 30', the magnetic declination at the time being 1° E. To what magnetic bearing should the line be set now if the present magnetic declination is 8° 30' E.
 - (A) 350° 00'

(B) 158° 00'

(C) 258° 00'

- (D) 58° 00'
- (E) Answer not known
- 47. The EDM (Electronic Distance Measurement) is based on
 - (A) Manual Chaining and Taping Techniques
 - (B) Theodolite readings and Angular measurements
 - Generation, Propagation, Reflection and Reception of Electromagnetic waves.
 - (D) Photographic Triangulation Method
 - (E) Answer not known

48.		•		veen two points on the plane he result was 468 m. Later,
				cale of 1 cm = 20 m. What is
	the	true distance be	tween the two point	S
	(A)	234 m	(B)	936 m
	(C)	468 m	(D)	874 m
	(E)	Answer not kr	nown	
49.	The	length of the li	ne measured with a	20 mtr. chain was found to

be 250 meters. Calculate the true length of the line if the chain was 10 cm to long? (A) 248.75 mtr. (B) 249.50 mtr. 251.25 mtr.

(D) 252.00 mtr.

- (E)Answer not known
- The full form of GIS is 50.
 - Geological Information System (A)
 - (B) Geodetic Information System
 - (C) Geographic Information System
 - Global Information System (D)
 - Answer not known (E)
- After an explosion in an underground Mine, the sampling of gases 51. should be done:
 - Only after full ventilation is restored (A)
 - After sealing the affected area (B)
 - As soon as the area is declared safe
 - Only from surface boreholes (D)
 - (E)Answer not known

52. What is the Ecolyser in the context of underground mining?			of underground mining?
	(A)	A ventilation system for fresh	air supply
	(B)	An intrinsically safe device for	
	(C)	A mechanical tool for breaking	
	(D)	A safety helmet for miners	
	(E)	Answer not known	
53.	The	purpose of a water seal in a stop	oping is to
	(A)	Drain water from behind	
	(B)	Allow water into the stopping	
	(C)	Balance pressures	
	(D)	Allow gases to come out	
	(E)	Answer not known	
54.	soun A st The	nd pressure level of 85 dBA at ops, the sound pressure level a	rating simultaneously produce a at a point. When the Machine at that point reduce to 80 dBA. same point due to Machine A
	(A)	70.0	(B) 75.0
	(C)	80.0	(B) 73.0 (D) 83.3
	(E)	Answer not known	(L) 00.0
55.		ch of the following gas is l mulate near the root of coal Min Carbon monoxide Carbon dioxide Answer not known	ighter than air and tends to nes? (B) Methane (D) Hydrogen sulphide

56.	3. How the coal seam is classified if emission rate of methane exceeds 10 m ³ /tonne of coal produced?			sion rate of methane exceeds
	(A)	First degree	(B)	Second degree
	Ces .	Third degree	02-2750	None of the above
	(E)	Answer not known		
	(—)			
57.		at is the chemical process call oxygen?	led '	when a substance combines
	(A)	Reduction	(B)	Neutralization
	(6)	Oxidation	(D)	Dissolution
	(E)	Answer not known		
58.		hydrogen sulphide is consi ing Environments?	.dere	ed extremely hazardous in
	(A)	It supports combustion		
	(B)	It is heavier than air and flam	ımal	ole
	Ses	It is extremely toxic		
	(D)	It is radioactive		
	(E)	Answer not known		
59.	leak resis calcu	n delivers 4 m ³ /sec of air through proof duct ventilating a head stance co-efficient $f = 0.02$ are alate the area of the orifice where the same quantity of air whose	ing. id d ich r	Taking the Darcy-Weisbach lensity of air = 1.2 kg/m ³ , may be used with the duct to
	(A)	$0.045~\mathrm{m}^2$	(B)	$0.060 \ m^2$
	40)	0.0747 m^2	(D)	$0.080 \ m^2$
	(E)	Answer not known		

60.	Which type of fans are underground coal mines/colling (A) Forcing fan (C) Pedestal fan (E) Answer not known	eries? (B)	the ventilation system in Exhaust fan None of the above
61.	pressure drop of 500 Pa acropressure of 300 Pa. What is	the area ts. Assume	sec of air respectively with a he Trunk airways consume a of the Regulator required to the fan pressure to remain 1.88 m ²
	(C) 2.22 m^2	(D)	3.00 m^2
	(E) Answer not known		
62.	A standard Pitot-Static tub diameter circular duct record the quantity of air flowing in K and the Barometer reads to the method factor to be equal	s a velocity the duct .08 KPa? (A	y pressure of 250 Pa. What is
	(A) 2.14 m ³ /s	(B)	$3.14 \text{ m}^3/\text{s}$
	(C) $4.14 \text{ m}^3/\text{s}$	(D)	$5.14 \text{ m}^3\text{/s}$
	(E) Answer not known		
63.	When an accumulation of fir coal mine, It is always advis flame safety lamp? (A) Flame test Accumulation test (E) Answer not known	sable to go	
		19	347-Mining Engineering [Turn over

- 64. What is true about blackdamp in terms of its physical properties?
 - (A) It is lighter than air and accumulator near the root
 - It is heavier than air and settler in low areas
 - (C) It is explosive and flammable
 - (D) It is composed mainly of methane and carbon monoxide
 - (E) Answer not known
- 65. Why explosion will not occur when the CH₄ percentage in underground mine atmosphere is more than 14.8%?
 - (A) Ignition temperature will increase
 - Percentage of oxygen will fall down
 - (C) Percentage of oxygen will go up
 - (D) None of the above
 - (E) Answer not known
- 66. A mine airway 2.1 meter wide 2.4 meter high and 600 meter long contains a bend of $\pi/3$ radians (angle of deflection) and radius of curvature of 3 meters. The shock factor for the bend is
 - (A) 0.0608

(B) 0.0508

(C) 0.0708

- (D) 0.0808
- (E) Answer not known

- 67. A 300 meter long airway in an underground mine passes 10 meter cube of air per second. The quantity of air passing through it when another airway of 250 meter long is added parallel is
 - 20.95 meter cube / second
 - (B) 2.095 meter cube / second
 - (C) 200.95 meter cube / second
 - (D) 0.2095 meter cube / second
 - (E) Answer not known
- 68. What is underground mine 'Relighting stations'?
 - Lamp stations for Relighting safety lamps
 - (B) Lamp stations for Relighting the Electric light
 - (C) Lamp stations for Restarting the Booster fan
 - (D) Lamp stations for Restarting the Auxiliary fan
 - (E) Answer not known
- 69. A standard pitot static tube placed at the centre of 500 mm diameter circular duct records a velocity pressure of 300 Pa. Calculate the quantity of air flowing in the duct if the air temperature 301 K and density of air is 1.2 kg per cubic meter. Assume the air to be dry and the method factor is 0.8
 - (A) $3 \text{ m}^3/\text{s}$

 $(B) 3.5 \text{ m}^3/\text{s}$

(C) $4 \text{ m}^3/\text{s}$

- (D) $4.5 \text{ m}^3/\text{s}$
- (E) Answer not known

Why auxiliary fan of forcing type is located in the airway atleast 9m 70. up stream of the corner of pillar at the junction of the heading to be ventilated? (A) To allow minimum deposition of dust To avoid recirculation of hot return air mixed with dust and gases (C) To avoid chances of any explosion To avoid mixing of intake and return air (D) Answer not known (\mathbf{E}) Which of the following is classified as a Naturally supported 71.STOPE? (B) Sub-level stopping (A) Cut and fill stoping (D) Top slicing (C) Shrinkage stoping (E)Answer not known 72.In block caving, the ore is broken by (A) Controlled blasting (B) Wedge-cutting Induced collapse of the ore body Top slicing (D)(E)Answer not known The sub-level caving is not preferred for high grade ore 73.(A) Poor ventilation (B)Low production rate High dilution due to mixing of ore and waste

Need for square sets

Answer not known

(D)

 (\mathbf{E})

74.	What is the purpose of sump in underground workings?					
	(A)	To store coal	(B)	To store explosives		
	(0)	To collect water	(D)	To improve ventilation		
	(E)	Answer not known				
75.	Whice mine	ch equipment is typically used es?	for	drivage in underground coal		
	(A)	Dragline	(B)	Road header		
	(C)	Shovel	(D)	Surface miner		
	(E)	Answer not known				
76.		ch of the following is an essentive to act as a cooling agent?	ntial	constituent of a permitted		
	(A)	Ammonium nitrate				
	(B)	Charcoal				
	(2)	Sodium chloride, potassium ch	ılori	de, or sodium fluoride		
	(D)	Diesel oil				
	(E)	Answer not known				
77.		ch of the following are considering considering the considering are considered as a considering considering the considering are considered as a considering considering considering are considered as a considering consid	dere	ed as "Fuel Sensitizers" in		
	(A)	Ammonium Nitrate and Urea				
	(B)	TNT, PETN and PENTOLITE	i			
	(C)	Diesel oil and Charcoal				
	(D)	Water and Gum				
	(E)	Answer not known				

The most effective and oxygen balanced Ammonium Nitrate-Fuel 78. Oil (ANFO) explosive mixture contain (A) 1-2% diesel oil by weight (B) _3-4% diesel oil by weight 5-6% diesel oil by weight 10-12% diesel oil by weight (D) Answer not known (\mathbf{E}) Which of the following is a white Hygroscopic salt, very soluble in 79. water and comparatively very safe to handle? (A) Gun powder (B) TNT Ammonium Nitrate Calcium Nitrate (C) (E)Answer not known When a low explosive is blasted, the process of oxidation is 80. propagated by Instantaneous detonation across the entire mass (A) Rapid combustion from particle to particle through the mass Slow thermal expansion without combustion (C) Absence of any shock wave (D) (E) Answer not known 81. Zero oxygen balance for an explosive is the state at which (A) Contains oxygen to form oxides of nitrogen Energy output is optimized (B) Contains oxygen to oxidize all fuels

(D)

(E)

No oxygen is left out for fuels

Answer not known

82.	Most	commonly used oxidisers for	explo	sives are					
	4	Ammonium nitrate, sodium nitrate and calcium carbonate							
	(B)	Carbon, aluminum and TNT							
	(C)	Carbon, sodium nitrate and TNT							
	(D)	Ammonium nitrate, sodium nitrate and aluminum							
	(E)	Answer not known							
	(-/								
83.	The	The shape formed by a pyramid cut is generally							
	(A)	Hexagonal	(B)	Triangular					
	(0)	Square or polygonal	(D)	Conical					
	(E)	Answer not known							
84.		Which explosive is most suitable for use in gassy underground coal mines?							
	(A)	Emulsion explosive	(D)	Permitted explosive					
	(C)	Slurry explosive	(D)	ANFO					
	(E)	Answer not known							
85.		ch drilling method is suitable sity and strength?	for ob	taining rock cores for testing					
	(A)	Diamond drilling	(B)	Cable drilling					
	(C)	Manual drilling	(D)	Percussion drilling					
	(E)	Answer not known							
86.	In pe	ercussion drilling, which part	actua	lly strikes the rock surface?					
	(A)	Water hose	(B)	Bit holder					
	40	Chisel	(D)	Clamp					
	(E)	Answer not known							
		25		347-Mining Engineering					

87.	Which is the correct arrangement of equipment for diamond drilling on surface?								
	(A)	Compressor, light, casing pipe, rod							
	(B)	Pump, hose, drill rod, detonator							
	(C)	Crane, blower, tank, engine							
	(B)	Derrick, engine, winch, water pump, settling tank							
	(E)	Answer not known							
88.	What is the function of the chamber screw in cable drilling?								
	(A)) To rotate the bit							
	(B)	To power the winch							
	(C)	To generate water pressure							
	(25)	To secure the rope to the clamp							
	(E)	Answer not known							
89.	Wha	t is the usual diameter range o	drill	holes in Mining areas?					
	(A)	100 mm to 250 mm	(D) 2	25 mm to 125 mm					
	(C)	150 mm to 300 mm	3	.0 mm to 50 mm					
	(E)	Answer not known	. /						
90.	The	The part of the mineral resource that can be economically mined is							
	4	Proved	(B) F	Proved and probable					
	(C)	Indicated	7.000 000 000 000 000 000 000 000 000 00	ndicated and probable					
	(E)	Answer not known		•					

91.	Whi	Which of the following has poor water resistant property?							
	(4)	ANFO	(B) Slurry explosive						
	(C)	Emulsion explosive	(D) NG based explosive						
	(E)	Answer not known							
92.		U							
		D							
		D							
	The	above symbol in a Geological n	napping indicates what?						
	nt of fault								
	(B)	Relative slip direction and plu	unge						
	(6)	Relative vertical movement of	of fault						
	(D)	Uncertain fault							
	(E)	Answer not known							
93.	Whi	ch mineral is the main constitu	uent of limestone?						
	(A)	Gypsum	(B) Dolomite						
	(C)	Quartz	(D) Calcite						
	(E)	Answer not known							
94.		ch rock type is formed by the sure on existing rocks?	e action of high temperature and						
	(A)	Igneous rock	(B) Sedimentary rock						

(C)

(E)

Plutonic rock

Answer not known

(D) Metamorphic rock

95. What is the typical silica content in basic rocks?				ic rocks?				
	(A)	More than 65%	(B)	45% to 55%				
	(C)	55% to 65%	(D)	Less than 45%				
	(E)	Answer not known						
96.	Which mineral gives a white streak and is a major component of marble?							
	(1)	Calcite	(B)	Dolomite				
	(C)	Gypsum	(D)	Quartz				
	(E)	Answer not known						
97.	Why is the ANFO mixture said to be less suitable in very wet or water-logged boreholes?							
	(A)	Low VOD						
	(B)							
	(0)	Ammonium nitrate absorbs w	ater	and reduces sensitivity				
(D) Difficult to prime with no. 8 detonation								
	(E)	Answer not known						
98.	Whic	ch element's less determines th	e 'Vo	platile matter'?				
	(A)	Calcium	(B)	Sulphur				
	(0)	Hydrocarbon gases	(D)	Silica				
	(E)	Answer not known						
99.	Wha	t is the typical calorific value (e	ev) o	f lignite?				
	(A)	6200 kcal/kg	(B)	3200 kcal/kg				
	10)	2400 kcal/kg	(D)	the contract seems of the contract seems and the contract seems and the contract seems are contract seems and the contract seems are contract seems and the contract seems are contract				
	(E)	Answer not known	sass fi	(=)				
347-N	Iining	Engineering 28						

100.	Which of the following is a lignite field?					
	(A)	Raniganj	(D)	Neyveli		
	(C)	Umaria	(D)	Sohapur		
22	(E)	Answer not known				
101.	Fixed	l carbon is calculated by				
	(A)	Adding ash and volatile matte	r.			
	(B)	Gravimetric analysis				
	(C)	Direct burning				
	(D)	Subtracting, moisture and vola	atile	matter from 100		
	(E)	Answer not known				
102.	Whic	h of these is NOT a method of J	prox	imate analysis reporting?		
	(A)	Unit - Coal basis	(B)	Air - dried basis		
	(4)	On - field basis	(D)	As - Received basis		
	(E)	Answer not known				
103.	Whic	h coal rank is considered the P	ures	t?		
	(A)	Peat	(B)	Lignite		
	(C)	Anthracite	(D)	Bituminous		
	(E)	Answer not known				
104.	What	t kind of fault has movement pa	arall	lel to the dip of beds?		
	(A)	Strike fault	(B)	Listric fault		
	(0)	Dip fault	(D)	Oblique fault		
	(E)	Answer not known				

105	Most	t major coal deposits formed du	ring which geological period?	
105.				
	(A)	Jurassic Cretaceous	(B) Triassic (Carboniferous)	
	(C) (E)	Answer not known	(arbointerous	
	(12)	Miswei not known		
106.	Whi	ch is not ore body modeling tec	hniques?	
	(A)	Triangle	(B) Polygon	
	(2)	Round	(D) Block	
	(E)	Answer not known		
107.		ch of the following paramete pping ratio in a pushback design	ers most directly influences the n?	
	(A)	Commodity price	(B) Pit slope angle	
	(C)	Milling cost	(D) Drill hole spacing	
	(E)	Answer not known	(a) =	
	N. P. C			
108.	Wha	t is the primary objective of mi	ne design?	
	(A)	To maximize dilution		
	(B)	To ensure safety, efficiency ar	nd economic viability	
	(C)	To reduce ore recovery		
	(D)	To increase environmental for	otprint	
	(E)	Answer not known		
109.		et value is N and grade is G, – 36+0.3, then cut off grade is	they are related by the equation	
	(A)	0.2	(B) 0.1	
	(C)	0.3	(D) 0.5	
	(E)	Answer not known		
347-Mining Engineering 30				

- 110. In a Block model, the block height is mostly
 - (A) Height of bench

- (B) Width of bench
- (C) Height/Width of bench
- (D) Thickness of deposit
- (E) Answer not known
- 111. He O' Hara cost estimator is used for
 - (A) Environmental impact assessments
 - Quick and dirty mining cost estimates
 - (C) Geotechnical slope stability
 - (D) Ore Reserve classification
 - (E) Answer not known
- 112. What is the main purpose of drilling in Mining?
 - (A) To stove explosives underground
 - (B) To improve ventilation only
 - (C) To reduce noise levels in Mines
 - To obtain information about rock structure and mineral beds
 - (E) Answer not known
- 113. Restoration, Reclamation and Rehabilitation of land shall be completed
 - (A) After abandoning mine
 - Before abandoning Mine
 - (C) Before handling over to NGO'S
 - (D) Prior to opening up a New Mine
 - (E) Answer not known

rate is 700,360, the mine life is			,000 tonnes, and the production							
	45	11.1 years	(B) 11.0 years							
	(C)	10.9 years	(D) 10.8 years							
	(E)	Answer not known								
115.	Sens	Sensitivity analysis in feasibility studies is primarily used to								
	(A)	Calculate slope stability								
	(B)	Compare competitor mine per	formance							
	9	Assess impact of varying key i								
	(D)	Design haul roads								
	(E)	Answer not known								
116.	A mine uses 4.5 BCM truck load. With a swell factor of 1.3 and fill factor of 0.9, what is the loose volume hauled per cycle									
		B – Bauk	L-Loose							
	(A)	4.2 LCM	(B) 5.26 LCM							
	(C)	4.95 LCM	(D) 6.5 LCM							
	(E)	Answer not known								
117.	Why	is a minimum turning radius i	mportant in haul road design?							
	(A)	To reduce grade control errors								
	(B)	To accommodate equipment m	aneuverability							
	(C)	To increase haulage speed								
	(D)	To improve blasting efficiency								
	(E)	Answer not known								

32

347-Mining Engineering

a

118.	3. What would be the likely consequence of using an excessively low cutoff grade in pit design?					
	(A)	Increased NPV				
	(B)	Reduced tonnage	N a			
	(0)	Pit enlargement beyond econo	mic limits			
	(D)	Better concentrate quality	,			
	(E)	Answer not known				
119.	The	use of stockpiling in open pit op	perations primarily affects			
	(A)	Overall pit slope				
	(B)	Drill pattern design				
	(6)	Economic performance via cut	off grade flexibility			
	(D)	Bench width				
	(E)	Answer not known				
120.		ch of the following is treated a ning and decision making?	as one of the important input of			
	(A)	Resource allocation	(B) Scheduling			
	(4)	Forecasting	(D) Capital budgeting			
	(E)	Answer not known				
121.	Gros	s domestic happiness (GDH) re	fers to which Index?			
	(A)	Index of Market Price	(B) Index of Poverty			
	(e)	Index of Progress	(D) Index of Literacy			
	(E)	Answer not known	± ± ± ± ± ± ± ± ± ± ± ± ± ± ± ± ± ± ±			
	one to Fee					

122.		ch feasibility study includes drate cost estimates.	etailed Engineering designs and
	(A)	Scoping study	(B) Pre-feasibility study
	(9)	Feasibility study	(D) Environmental study
	(E)	Answer not known	
123.		ch of the following is not typica ort (DPR)?	lly included in a Detailed Project
	(A)	Environmental clearance docu	imentation
	(B)	Final pit slope validation	
	(C)	Capital and operating cost est	imates
	(D)	Project implementation sched	ule
	(E)	Answer not known	
124.	Wha stud		wn Structure (WBS) in feasibility
	(A)	Defines are grade requiremen	ts
	(B)	Outlines environmental comp	
	(0)		e into logical work per changes
	(D)	Estimates Labour requiremen	
	(E)	Answer not known	
125.	perio		tages and for each stage the time 04 years, 5 years, 6.04 years and
	(A)	20.6 years	(B) 19.6 years
	40)	21.6 years	(D) 22.1 years
	(E)	Answer not known	

- 126. When mineral is extracted from an underground mine the void (Goaf) is perched with sand or other perching material. This process is called as
 - (A) Roof bolting
 - (B) Subsidence control
 - (C) Grouting
 - (D) Showing
 - (E) Answer not known
- 127. A rock sample has bulk density of 2.89 GM/CC. IFS moisture content was found to be 1.38%. It's dry density will be
 - (A) 2.52 GM/CC

(B) 2.69 GM/CC

(e) 2.85 GM/CC

- (D) 2.96 GM/CC
- (E) Answer not known
- 128. (i) The creep has got three parts: Primary; Secondary and tertiary creep
 - (ii) Primary creep is followed by tertiary and secondary creep
 - (iii) Tertiary creep is followed by primary and secondary creep
 - (iv) Primary creep is followed by secondary and tertiary creep Out of the above statement
 - (A) (i) and (iii) are correct
- (B) (i) and (ii) are correct
- (i) and (iv) are correct
- (D) None is correct
- (E) Answer not known

129.	29. In Mohr's circle of stresses the angle between principal plane maximum shearing plane is				
	(A)	90 degree	(B)	180 degree	
	(C)	360 degree	(D)	45 degree	
	(E)	Answer not known			
130.	In re	sin bolting, gel time refers to th	ie ti	me	
	(A)	Before inserting capsule			
	(B)	To drill the hole			
	(2)	Between spinning and harden	ing		
	(D)	To insert bolt			
	(E)	Answer not known			
131.	CMR	S hydraulic props include whic	h sa	fety feature?	
	(A)	Ventilation pipes	(B)	Shear pins	
	(4)	Safety release valve	(D)	Expansion shell	
	(E)	Answer not known			
132.	What	t is the compressive strength of	cur	ed resin?	
	(A)	25 MN/m ²	(B)	$50 \mathrm{\ MN/m^2}$	
	(0)	125 MN/m ²	(D)	$10 \mathrm{\ MN/m^2}$	
	(E)	Answer not known	25 12		
133.	Whic	h prop type is unsuitable in un	ever	n root seams?	
	(A)	Resin bolt	(B)	Bamboo bolt	
	405	Steel Joist prop	A A	Concrete set	
	(E)	Answer not known	(-)	<u> </u>	

							9
134.	Wha	at is tl	ne fun	ction o	f a canti	lever	bar in powered supports?
	(A)	To s	uppor	t imme	ediate ro	ot	(B) To Support the goaf
	ies	•			units		(D) To transmit hydraulic fluid
	(E)			t knov			
	(-)		AL SER DES				
195	T _m o	, hous	hala la	or of 1	Om in 1	on otl	n magazing of mode cover in am is
155.							n, recovery of rock cores in cm is 3 , 9 , 10 , 1 , 5 , 10 . The RQD ir
		centag		, 0, 1	.5, 5, 5,	-,	., 0, 10, 1, 0, 10. 11. 11. 11.
	K	29.2					(B) 31.8
	(C)	45.8					(D) 50.0
	(E)			t knov	wn		(2) 33.3
	(11)	11110	WOI III	70 IXIIO V	, 11		
100	3.5		0.11				
136.	Mat		e follov	ving			
	1000000	0.530	oment				Component
	(P)	Scraper				1.	Dribble belt
	(Q)	Drag				2.	Dipper stick
	(R)	Buck	et whe	eel Exc	avator	3.	Fair lead
	(S)	Rope	shove	l		4.	Bowl
		(P)	(Q)	(R)	(S)		
	(A)	2	4	3	1		
	(B)	4	2	1	3		
	(8)	$^{2}4$	3	1	2		
	(D)	2	4	1	3		
	(E)	Ansv	wer no	t know	vn		

137.	The rate at which a machine component oscillates is called				
	(A)	Speed of machine			
	(B)	Vibration frequency			
	(C)	RMS frequency			
	(D)	Indicator of machine condition			
	(E)	Answer not known			
138.	38. The volume of a given mass of gas varies inversely as the absolute pressure when the temperature remains constant. The relationship is described by which of the following lawn.				
	(K)	Boyle's law (B) Charles law			
	(C)	Avagadro's law (D) Gay-Lussae's law			
	(E)	Answer not known			
139.	In a core. (A) (B) (C) (D) (E)	Opposite to the threads of a right hand Screw Perpendicular to the rope axis In the same direction as the threads of a right hand screw Randomly arranged around the core Answer not known			
140.	Wha (A) (B) (C) (D) (E)	t is the defining characteristic of an epicyclic gear Train? All gears are fixed and rotate about the same axis There is no motion between gear axes There is relative motion between the axes of the shafts It can only be used in vertical shafts Answer not known			

- 141. As per DCF analysis a project report is acceptable if
 - (A) Discounting rate > IRR
 - Discounting rate < IRR
 - (C) Discounting rate = IRR
 - (D) There exist no relation between the two
 - (E) Answer not known
- 142. A mining project requires an investment of Rs.100 million and will generate annual cash flows of \$.20 million for 7 years. If the IRR is estimated to be 12%. Which of the following statements is true?
 - (A) The project should be accepted if the required return is 10%
 - (B) The project should be rejected if the required return is 15%
 - (C) The project's NPV is negative if the discount rate is 12%
 - Both (A) and (B) are correct
 - (E) Answer not known
- 143. If inflation increases unexpectedly during a mining project, what is its likely effect on NPV?
 - (A) NPV increases

(B) NPV remains constant

(C) NPV decreases

- (D) NPV turns negative
- (E) Answer not known

144. A Mining project has the following cash flows

Year	Cash flow (\$M)		
0	-50		
1	15		
2	18		
3	14		
4	12		
5	10		

What is the payback period for the project?

(A) 2.75 years

(B) 3.0 years

(**2**) 3.25 years

- (D) 3.5 years
- (E) Answer not known
- 145. A Mining project has an initial investment of \$75 Million and the present value of future cash flows is \$90 million. If the discount rate increases, what will happen to the PI?
 - (A) PI will increase
 - B PI will decrease
 - (C) PI will remain the same
 - (D) PI will become negative
 - (E) Answer not known
- 146. China clay, Fireclay and Ballclay are
 - (A) Coproducts of Lignite
- (B) Byproducts of Lignite
- (C) Coproducts of coal
- (D) Byproducts of coal
- (E) Answer not known

147.	If Rs.10,000 is invested in a bank at the end of each year for a period of 5 years, the present value of these payments is			
	(A)	Rs. 37,090	(B)	Rs. 37,900
	(C)	Rs. 36,900	(D)	Rs. 36,090
	(E)	Answer not known		
148.	If the	e discount rate increases, what ct?	hap	pens to the NPV of a mining
	(A)	NPV increases	(B)	NPV remains unchanged
	(0)	NPV decreases	(D)	NPV turns positive
	(E)	Answer not known		
149.	A mining company processes ore at a cost of \$ 50 per ton. The price of the metal is \$ 500 per ounces, and the recovery rate is 85% if each ton of ore contains 0.15 ounces of metal, what is the cut - off grade (minimum ore grade to be profitable)			
	(A)	0.10 ounces per ton	(B)	0.12 ounces per ton
	(C)	0.15 ounces per ton	(D)	0.08 ounces per ton
	(E)	Answer not known		
150.	A mi	ning project shall be accepted o	r op	erated if
	(A)	NPV is Negative	(B)	NPV is Zero
	(0)	NPV is positive	(D)	NPV is unpredictable
	(E)	Answer not known		

151.	Use of power in a mine shall be at a voltage of		
	(4)	Not more than 6600 V	(B) More than 6600 V
	(C)	Both (A) and (B)	(D) None of the above
	(E)	Answer not known	
152.		hich regulation of CMR 1957 lated?	, the duties of safety officers is
	(A)	41	(B) 41 (A)
	(C)	42	(D) 42 (A)
	(E)	Answer not known	
153.		econd or third degree gassy ratus is permitted by	mine use of electric welding
	(A)	Colliery Manager	(B) Agent
	(6)	Regional Inspector	(D) Director (Technical)
	(E)	Answer not known	
154.			nspectors are mandated in mines
		187	employed in the mine is equal to
	orex	ceeds?	(D) 1000
	(A)	500	(B) 1000
	(C)	1500	(D) 2000
	(E)	Answer not known	

155.	As per 10 th National conference on safety in mines, what is the test stipulated for canteen workers in the mines and what is the periodicity of such test?					
	4	Stool and sputum test, once in	ever	y six mor	nths	
	(B)	Tuberculosis test, once in a ye		-		
	(C)	Eye test, once in every six mor	nths			
	(D)	Periodic medical examination,	once	in 3 year	rs	
	(E)	Answer not known				
156.	. A first-aid room is required at a miner when the number of persons employed on any given day in the previous calendar year is more than ————?					
	W	150				
	(B)	200				
	(C)	250				
	(D)	300				
	(E)	Answer not known				
157.	. In the interest of safety, the earth fault current shall not be more than milliampere in installations of voltage exceeding 250 V and upto 1100 V for below ground mines and oil fields?			age exceeding		
	(4)	750 mA	(B)	1000 mA		
	(C)	1500 mA	(D)	2000 mA		
	(E)	Answer not known				

158.	As per CEAR 2023, electricity shall	not be tran	smitted into	a below
	ground mine at a voltage exceeding	11000 V a	nd shall not	be used
	therein at a voltage exceeding —	?		

- (A) 6000 V
- (B) 3300 V
- (C) 250 V
- (D) 440 V
- (E) Answer not known
- 159. A miner finds that an unused flexible cable is still energized in an underground mine. According to CEAR 2023, what action should be taken?
 - (A) Secure the cable properly
 - (B) Immediately detach or isolate the cable from supply
 - (C) Wrap the cable with insulation tape
 - (D) Allow it to remain energized if no one is working nearby
 - (E) Answer not known
- 160. As per Reg. 96 (Haulage rope) of CMR 2017, every rope which is capped shall be recapped once atleast in how many months?
 - Every Six months
 - (B) Every Eight months
 - (C) Every Nine months
 - (D) Every Twelve months
 - (E) Answer not known

161.	As per coal mines regulations an automatic contrivance shall b provided for winding in a shaft of depth exceeding.			
	(A)	50 m	(B)	100 m
	(C)	150 m	(D)	500 m
	(E)	Answer not known		
162.	- 1	er coal mines regulations the ing of a seam and an active fire		
	(A)	30 meters	(B)	45 meters
	SES	60 meters	(D)	100 meters
	(E)	Answer not known		
163.	-	er coal mines regulations, to arison with the hole depth sha		379.
	(A)	less than 20 centimeter in leng	gth	
	(B)	less than 5 centimeter in lengt	th	
	(C)	less than 10 centimeter in leng	gth	
	(20)	less than 15 centimeter in leng	gth	
	(E)	Answer not known		
164.	every inspe	er Regulation 4 of emr 2017, y year, the owner, agent or mector the regional inspector al Returns in respect of the pr	anag end	ger shall submit to the chief to the District Magistrate
	(A)	Form - I	(B)	Form - 2
	(e)	Form - 3	(D)	Form - 4A
	(E)	Answer not known		

165.	perm		on safety in Mines, what is the n mines in case percentage of free
	(A)	3.0 mg/m^3	(B) 1.0 mg/m ³
	(C)	2.0 mg/m^3	(D) 5.0 mg/m ³
	(E)	Answer not known	
166.		vehicle transporting the explo speed exceeding.	sives in Bulk shall not be driven
	(A)	20 kmph	(B) 30 kmph
	405	25 kmph	(D) 35 kmph
	(E)	Answer not known	
167.		t does DGMs (Tech) circular ide for?	No. 10 of 2020 dated 23/06/2020
	(A)	Guidelines to prevent occurre	ence of incidents due to vehicle in
	(B)	Guidelines to prevent occurre in mines	ence of incidents due to explosives
	(C)	Guidelines to prevent occurre	ence of incidents due to HEMM in
	(D)	Guidelines to prevent occurre in mines	ence of incidents due to lightning
	(E)	Answer not known	
168.		fety committee must be consti	tuted in every mine where more ordinarily employed.
	(A)	500	(B) 1000
	40)	100	(D) 300
	(E)	Answer not known	15 [0.
347-Mining Engineering 46			

169.	In m	ine, the electrical supervisor is	appointed by
	(A)	DGMS	
	(B)	Electrical Inspector	
	40	Owner, Agent or Manager of the	he Mine
ii.	(D)	Chief Engineer	
8	(E)	Answer not known	
170.		t type of switch gear is requi ly in mines?	red for disconnection of power
	(A)	Manual fuse box	
	(B)	Properly constructed switch ge	ear
	(C)	Circuit breakers only	
	(D)	Residual current devices	
	(E)	Answer not known	
171.		coal mine, if 1800 tonnes were nes, how many man shifts were	produced in a day with an oms of e worked?
	(A)	200	(B) 250
	(2)	300	(D) 400
	(E)	Answer not known	
172.		t is the main objective of a T ace mining?	ruch Dispatch System (TDS) in
	(A)	To increase drilling efficiency	
	(B)	To improve are blending	
	(0)	To optimize haulage operation	and deduce idle time
	(D)	To monitor explosive usage	
	(E)	Answer not known	

- 173. In an opencast mine, 38 levels and 12 dumpers are working. Each dumper carries 15 tonnes per trip and makes 8 trips per shift. Calculate daily output assuming 1 shift per day.
 - (A) 1460 tones/day

(B) 1480 tones /day

(C) 1490 tones /day

(2) 1440 tones/day

- (E) Answer not known
- 174. A dragline is required to remove 3,00,000 m³ of rock per month on the bank volume basis. Consider the following data for the dragline operation.

Effective working hour per month = 450

Bucket fill factor = 0.8

Cycle time = σ 5 S

Swell factor of the rock = 1.25

The minimum bucket capacity of the dragline in m³ is:

(A) 7.70

(B) 9.63

(C) 12.04

- (B) 18.80
- (E) Answer not known
- 175. An opencast mine has four benches. The height, width and face angle for each bench are 13 m, 30 m and 70° respectively. The overall slope angle of the benches in degree is
 - (A) 25.5°

(B) 20.7°

(C) 33.4°

- (D) 19.7°
- (E) Answer not known

- 176. In placer mining in the technique of hydraulicking the following is an optional parameter in that process
 - (A) Adequate water supply
 - (B) Material disintegrated by water action
 - Independent of hydraulic gradient
 - (D) Space for waste disposal
 - (E) Answer not known
- 177. Productivity of machine is defend on
 - (A) Available hour
 - (B) Utilization hour
 - (C) Breakdown hour
 - (D) Repair hour
 - (E) Answer not known
- 178. The major reason for converting under ground mine to surface mine is
 - (A) Highly mechanized machinery availability
 - (B) Gases
 - (C) Ventilation
 - (D) Roof problem
 - (E) Answer not known

179.	In ul	In ultimate pit limit analysis, the most widely used method is		
	(A)	Dynamic programming		
	(B)	Linear programming		
	(6)	Simulation		
	(D)	Heuristic technique		
	(E)	Answer not known		
180.	Whic	h is not stabilization strategies?		
	(A)	Flattening of overburden scope		
	(B)	Scaling of loose material		
	(C)	Providing drain pipes or holes		
	(D)	Blasting		
	(E)	Answer not known		
181.	Whic	h not example of placer mining		
	(A)	Gold		
	(B)	Gemstone		
	(C)	Alluvial deposit		
	(B)	Diamond		
	(E)	Answer not known		
182.	Slope	e failure at bench in surface mining is		
	(A)	Circular (B) Toppling		
	(C)	Earthquake Wedge		
	(E)	Answer not known		

- 183. The side casting system adopted by draglines can be broadly classified into which of the following groups?
 - (A) Cross-pit, rotary, twin bucket, overhead
 - Simple, extended bench, horseshoe, Tandens
 - (C) Inclined, Horizontal, vertical, spiral
 - (D) Offset, swinging, oscillating, circular
 - (E) Answer not known
- 184. A haul ramp of 6% grade is to be constructed connecting a bench of 15 m height to the surface. If the cost of ramp construction is 1 million rupees per km, the cost of this ramp construction in million rupees will be?


(A) 0.25

(B) 0.10

(C) 2.50

(D) 0.50

- (E) Answer not known
- 185. Which of the following is an excavator which has a boom one end of which is attached with the revolving unit of the machine and the hanging end in the other side carrier a large sheave for the cable attached with the bucket?



- (B) Shover
- (C) Backhoe excavator
- (D) Bucket wheel excavator
- (E) Answer not known

- 186. Which type of rock is most suitable for ripping operations?
 - (A) Very hard igneous rock
 - Stratified rocks with hardness below 5 on Mohr's scale
 - (C) Mohr's crystalline rocks above 7 on Mohr's scale
 - (D) Unweathered quartzite
 - (E) Answer not known
- 187. Why it is essential to extend vertical or inclined blast holes slightly beyond the bench floor in hard rock?
 - (A) To reduce drilling time
 - (B) To allow for drainage
 - To ensure proper fragmentation of the toe
 - (D) To reduce fly rock generation
 - (E) Answer not known
- 188. What is the term used to describe the proportion of overburden to coal/mineral removed in mining?
 - (A) Recovery factor
 - (B) Stripping ratio
 - (C) Grade
 - (D) Yield
 - (E) Answer not known

- 189. For OB removal with shovel dumper combination, the optimum size of the dumper depends on
 - (A) Distance of the haul
 - (B) Size of the shovel
 - Distance of the haul and size of the shovel
 - (D) Tonnage to be handled
 - (E) Answer not known
- 190. The mining method that defines the production of a stone/aggregate is
 - (A) Quarrying
 - (B) Dimension stone mining
 - (C) Small scale mining
 - (D) Open cast mining
 - (E) Answer not known
- 191. A bucket wheel excavator has 14 buckets rotating at 15 revolutions per minute. Each bucket has a capacity of 700 liters with a fill factor of 0.8. The hourly production with an efficiency of 90% and mineral density of 1.2 meter cube/Tonne is
 - (A) 762.048 Tonnes/hour
 - 7620.48 Tonnes/hour
 - (C) 76.2048 Tonnes/hour
 - (D) 7.62048 Tonnes/hour
 - (E) Answer not known

192.	mate		sed with a 400 Tonne truck for a eter cube. The number of shovel actor of 0.8
	(A)	3	43 2
	(C)	4	(D) 5
	(E)	Answer not known	
193.		agline has a bucket capacity of . How much material will it mo	50 m³ and completes 4 cycles per ove in a 10 hour-shift?
	(A)	1500	(B) 1800
	(0)	2000	(D) 2500
	(E)	Answer not known	
194.	time	per truck is 5 min, and truck th factor 0.66 1.2	are assigned. The shovel loading k cycle time is 20 min. Calculate (B) 1
	(E)	Answer not known	
195.	shov rock	el of 5 m³ bucket capacity, is 6	ore, if loading cycle time-of the 0 seconds, bucket fill factor is 0.8, d shovel working time utilization t of the shovel, m ³ /hr would be
	(A)	93	(B) 94
	(C)	95	(10) 96
	(E)	Answer not known	

196.	Whic	Which is not surface mining method?		
	(A)	Opencast method	(B) Bord and pillar method	
	(C)	Strip mining	(D) Quarry	
	(E)	Answer not known		
197.		t should be Idle stripping rat g shovel-dipper/Dumper combir	io for mechanised surface mine	
	(A)	1:1.5	(B) 1:2.0	
	(C)	1:3.0	(B) 1:4.0	
	(E)	Answer not known		
198.	The r	maximum Haul-Road gradient	in India	
	(A)	1:10	(B) 1:12	
	(C)	1:14	(B) 1:16	
	(E)	Answer not known		

- 199. "Which is the continuous surface miner?
 - (A) Shovel
 - (B) Dragline
 - (C) Ripper dozer
 - Bucket wheel excavator
 - (E) Answer not known

200. Layout of mechanized surface mine is not depend on

- (A) Dip of deposit
- (B) Thickness of overburden
- (C) Shape of the deposit
- Compressive strength of deposit
- (E) Answer not known